[WebApp] Protocal22-API □□□ (PHP)

> “
>
> [WebApp] PROTOCOL22-API □□□

□□□□ □□

□□□□ Dabory OwnerKey API for WebApp□ Main App□ Guest App□ □□□ □ □□□ □□ □□□ □□□□ PHP Laravel□ □□□ WebApp□□□ PROTOCOLI22-API□ □□□□ □□□ □□□□□.

WebApp □□□ Owner Key API □□ □□

1. .env □□□ □□□□□ □□□□□.

2. Laravel callOwnerApi() □□□ □□ Owner APP□ □□□ API □□□ □□□ □□□□.

3. □□□ □□□ GateToken□ frontUrl □□□ □□□□ API □□□ □□□□.

4. API □□□ □□ □□□□ □□□□□.

WebApp □□□□

- env □□□ □□□□ □□

□□ .env □□□ OwnerKey □ APP □□□ □□□□□□□.

□□□□ □□□□ □□ □□□ □□□□ □□□□ □□□ □□□ MAIN APP□ 2□ □□□□□

□□□ □□ □□ □□ _ □□□ □□□□ □□□□ □□□□□□.

```
# [protocol22]
OWNER_APP_NAME=YOUR_OWNER_APP_NAME  # Owner APP의 이름 (대소문자 구분)
GUEST_APP_OWNER_KEY=YOUR_OWNER_KEY  # Guest APP에서 사용하는 OwnerKey 값
GUEST_APP_OWNER_URL=YOUR_OWNER_URL  # Owner APP의 URL 주소 (ex.www.daborysso.com)

OWNER_APP_NAME2=YOUR_OWNER_APP_NAME_2
GUEST_APP_OWNER_KEY2=YOUR_OWNER_KEY_2
GUEST_APP_OWNER_URL2=YOUR_OWNER_URL_2

OWNER_APP_NAME3=YOUR_OWNER_APP_NAME_3
GUEST_APP_OWNER_KEY3=YOUR_OWNER_KEY_3
GUEST_APP_OWNER_URL3=YOUR_OWNER_URL_3
```

OwnerKey?

- OwnerKey는 **GUSET APP과 MAIN APP의 API**
- WebApp

- Laravel Owner API

callOwnerApi()

```
public function callOwnerApi($request)
    {
        // 전달된 'type'에서 숫자 추출 (guest[1] → 1)
        preg_match('/\d+/', $request['type'], $matches);
        $index = isset($matches[0]) ? (int) $matches[0] : null;

        // 세션에서 API URL 및 GateToken 가져오기
        if ($index !== null) {
            $apiUrl = session("OwnerGateToken.guest")[$index]['frontUrl'] ?? null;
            $gateToken = session("OwnerGateToken.guest")[$index]['gateToken'] ?? null;
        }

        // API 요청 URL 설정
        $request['url'] = $apiUrl . '/' .$request['url'];
        $request['headers'] = ['GateToken' => $gateToken];
        return $this->callApi($request);
    }
```

- API □□ □□

API□ □□□□ remote-signup-setup-get api□ □□□□ □□□□ □□□□□.

```
$officeInfo = $this->callApiService->callOwnerApi([
    'url'  => 'remote-signup-setup-get', // api □□□ □□□ api url
    'data' => [  // □□□ data
        'SetupCode' => 'passwd-policy',
        'BrandCode' => 'member',
    ],
    'type' => 'guest[1]' // env□ □□□□ owner app□ □□□ session□ □□□□ □□□ index□ □□
]);
```

□□ Dabory Protocol22-API for WebApp□□□□□□□**API**□□□□.

Revision #20
Created 3 March 2025 09:55:13 by □□□
Updated 20 March 2025 12:05:38 by □□□