□□□□□ □□ □□ □□□□ □□

api test tool□ □□□□ □□□□□ □□ □□ □□□ □□□ □□ □□ □ □□□□.

□□□□□ vscode□ Thunder Client□ □□□□□□.

kbgolf theme□ □□□□□□ □□□ QueryName□□ □□ □□□□□□□□.

□□ □□□ □□□□ □□ db□ □□□ GateToken□ □□□□□.

□□□□
□□□□ □□□□□ □□□□

□ □□□□□ □□□□ □□□□□□ □□□□□.

□□ □ □□□□□□ □□□□ dbr02 □□□□ □□□ □□□□□.

MAIN_API_URL □□ □□□ □□ url□ □□□□□. □□□□□□ □□□□□□
General □□ □ pap api□ □□□□ □□□ □□□□ url□□□.

□□□□ □□□ □□ url□ □□□□ □□□□.

```
http://13.124.2.254:18080/list-type1-page
```

headers□ □□□ GateToken□ □□□□□□.

Body 입력내용.


```json
{
  "ListType1Vars":{
    "FilterDate": "mx.pc6",
    "StartDate": "19900101",
    "EndDate": "21001231",
    "IsDownloadList": true
  },
  "QueryVars":
  {
    "QueryName": "kbgolf::download/post/post-sise",
    "FilterName": "",
    "FilterValue": "",
    "SimpleFilter": "mx.post_type_id=59",
    "SubSimpleFilter": "",
    "TestMode": "query"
  },
  "PageVars":{
    "Limit":10,
    "Offset":10
  }
}
```

시세를 입력할 항목은 post로 조인해 가져온다.

```
Status: 607 status code 607    Size: 510 Bytes    Time: 60 ms

Response    Headers 5    Cookies    Results    Docs                                          {}

1    [QueryTestMode]
2    ===/home/kbgolf/public_html/dabory/themes/kbgolf/qry/erp/list/list-type1/download/post
        /post-sise/subqry/insert1.sql===
3
4    INSERT INTO dbt_list_type1  ( created_on, list_token, id,
5        c1, c2, c3, c4, c5,
6        c6, c7, c8, c9, c10 )
7
8    SELECT UNIX_TIMESTAMP(), ?, id,
9            post_title, pc1, pc2, pc3, pc4,
10           pc5, STR_TO_DATE(pc6, '%Y%m%d') AS pc6, post_type_id, post_slug, post_no
11
12   FROM pro_post as mx
13
14
15   where true  and mx.post_type_id=59  and mx.pc6 between '19900101' and '21001231'
16   -- @order
17
18
19   ===
```

위와 같이 시세가 있도록 설정하면 완성이다.

Revision #4
Created 9 July 2024 04:26:13 by 서오석
Updated 10 July 2024 03:21:40 by 서오석