[illegible] Limit [illegible] [illegible]

1. [illegible] [illegible] : Limit[illegible] IsntPagination

[illegible]

- `QueryVars.IsntPagination = true`[illegible] [illegible] [illegible] [illegible]
- `vRet.PageVars.Limit` [illegible] [illegible]`1000000000`)[illegible] [illegible]

[illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible]

- [illegible] [illegible] [illegible]
- [illegible]:[illegible] `Limit` [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible].

2. [illegible] [illegible]

`IsntPagination` ListType1 [illegible] `Limit = 0` [illegible]. [illegible]

(Limit > 500 [illegible] 0[illegible] [illegible])

[illegible] [illegible] :

- [illegible] `IsntPagination` ListType1 [illegible] [illegible] [illegible] [illegible] [illegible].
- [illegible] `Limit = 0` [illegible] [illegible] [illegible] [illegible] [illegible] [illegible].
- [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible].

3. Query File[illegible] Limit [illegible]

[illegible] `LIMIT` [illegible] `OFFSET` [illegible] [illegible] [illegible]. ([illegible] [illegible] [illegible] [illegible] [illegible] [illegible])

```
SELECT
    mx.id as id,
    turbo_thumb as c1,
    item_name as c2,
    item_slug as c3
FROM dbr_item as mx
    INNER JOIN dbr_igroup as mb ON mx.igroup_id = mb.id
-- @where
```

limit 1

LIMIT □ □□□ **OFFSET**)□□□□□□□□ □□□□ □□□□□ □□ □□□□ □□□□□ □□□□ □□ □□□□ □□□□□□.

Revision #8
Created 17 January 2025 05:34:43 by □□
Updated 17 January 2025 06:27:36 by □□