[illegible] [illegible] [illegible]

MacOS[illegible]

1. [illegible]

[illegible](Crystal Reports) **PDF, Excel, Word** [illegible] **ERP,** [illegible] **, CRM,** [illegible]

2. MacOS[illegible]

MacOS[illegible]

2.1 Microsoft [illegible]

MacOS[illegible] RDP(Remote Desktop Protocol) [illegible] **Microsoft** [illegible], [illegible]

- [illegible]**:**

  Microsoft Remote Desktop (App Store)

2.2 [illegible]

1. **Microsoft Remote Desktop** [illegible].
2. **'Import from RDP File'** [illegible] '[illegible]' [illegible].
3. [illegible]**RDP** [illegible]
4. **Username([illegible])**[illegible] **Password([illegible])**[illegible] [illegible]
5. [illegible].



Enter Your Credentials

These credentials will be used to connect to [redacted].amazonaws.com (remote PC).

Username: Administrator

Password:

☐ Show password

3. [illegible] [illegible] [illegible]

[illegible] `.rpt` [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible], [illegible] [illegible] [illegible] [illegible]


Crystal Reports - [adjustment.rpt]
File Edit View Insert Format Database Report Window Help
Gulim
11
100%
1번
2번
3번
Report Explorer
Text35: 등록번호
Text36: 상 호 명
Line17
c12: headFoot.c1
c32: headFoot.c3
Text15: 영수증(연말정
Line18
Text38: 전화번호
Design
Report Header
@Time (Now)
영수증(연말정산)
@URL
등록번호
c1
전화번호
c2
고객번호
c5
Field Explorer
Database Fields
Formula Fields
Parameter Fields
Running Total Fields
Group Name Fields
Special Fields

1. [illegible] [illegible] (Text Box)

[illegible]:

- [illegible] [illegible]([illegible])[illegible] [illegible] [illegible] [illegible]
- [illegible] `"[illegible]` `"[illegible]"` `"[illegible]"` [illegible]

2. [illegible](Line) [illegible] [illegible]

[illegible]:

- [illegible] [illegible]([illegible])[illegible] [illegible] [illegible] [illegible] [illegible] [illegible], [illegible] [illegible](Line)[illegible] [illegible] [illegible]
- [illegible]: [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible]

3. DB [illegible] (Database Fields) - [illegible] [illegible] [illegible]

[illegible]:

- DB[illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible]
- [illegible] `{c1}` → `"[illegible]` `{c2}` → `"[illegible]"` [illegible] [illegible] [illegible]

4. [illegible] [illegible] [illegible] [illegible] [illegible] [illegible]

[illegible]: ex) [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible] [illegible]

- **DB[illegible] [illegible] [illegible](Details)[illegible] [illegible] [illegible] [illegible], [illegible] [illegible] "[illegible]"[illegible] [illegible] [illegible] [illegible]**
- **Header, Details, Footer[illegible] [illegible] `position` [illegible],[illegible] [illegible]**
- **`Section Expert` [illegible] `Suppress` [illegible] [illegible] [illegible] [illegible] [illegible] [illegible]**

---

1. [illegible] [illegible] [illegible] [illegible] Footer([illegible]) [illegible] [illegible] [illegible]

□□□:

- **Details(□□)□□ □□□□ □□□□□ Report Footer(□□) □□□ □□□□ □□□ □□□**
- **Report Footer□ □□**


Crystal Reports - [adjustment.rpt]
File Edit View Insert Format Database Report Windo
Gulim
11
1번
2번
Report Explorer
Text35: 등록번호
Text36: 상 호 명
Line17
c12: headFoot.c1
c32: headFoot.c3
Text15: 영수증(연말정
Line18
Text38: 전화번호
Text39: 대 표 자
Line20
c23: headFoot.c2
c42: headFoot.c4
Text40: (인)
URL1: @URL
Line19
Text41: 고객정보
Line21
Line22
Text42: 고객번호
Text43: 고 객 명
Line24
c61: headFoot.c6
c52: headFoot.c5
Page Header
Group Header #1: @SEQ N
Line34
Details
Line26
Text50: 방문일
Line35
c13: body.c1
Line27
Box1
Text51: 현금
Line28
c33: body.c3
Line30
Text52: 카드
c21: body.c2
Design
Report Header
Details
Group Footer #1:
Report Footer
Report Header

□□□ □□:

1□"Section Expert"□□ Report Footer □□ □□

- Report Footer□ □□ `"Section Expert"` □□
- `"Print at Bottom of Page"` □□ **□□!**
- `"Keep Together"` □□(!□□□ □□ □□□□ □□□ □□□ □□)

2□Suppress □□ □□□□ Report Footer□ □□□□□ □□□□ □□

- Report Footer □ `"Suppress"` □ `X-2` □□
- □□ □□□ □□

  `NOT ONLASTRECORD`
- **□□□ □□ □□□ □□□□ "□□"□ □□□!**

□□□ □□:

No	□□□	□□	□□	□□□□	□□
1	2024-11-10	10,000	50,000	0	60,000
2	2024-11-11	5,000	40,000	0	45,000
3	2024-11-12	8,000	35,000	0	43,000
	□□	**23,000**	**125,000**	**0**	**148,000**

✔ [illegible]

5. [illegible] Database Fields[illegible]

[illegible]:
➡ [illegible] **`Database Fields`** [illegible]

---

1. `Database Fields`[illegible]

[illegible]:
1[illegible] **`Field Explorer`** [illegible] **`"Database Fields"`** [illegible]
2[illegible]([illegible] `{c1}`, `{c2}`, `{c3}` [illegible])
3[illegible] **(Report)** [illegible]

---

2. [illegible] Header, Details, Footer[illegible]

[illegible]:
✔ **Header([illegible]) [illegible]:**

- `{position} = "head-foot"` [illegible], [illegible]
  ✔ **Details([illegible]) [illegible]:**
- `{position} = "body"` [illegible]
  ✔ **Footer([illegible]) [illegible]:**
- `{position} = "head-foot"` [illegible]

---

3. [illegible]: Database Fields [illegible]

[illegible]Report [illegible]

[illegible]	Database Fields ([illegible])	[illegible]
Header	`{c1}` ([illegible])	[illegible]
Header	`{c2}` ([illegible])	[illegible]
Details	`{c3}` ([illegible])	[illegible]
Details	`{c4}` ([illegible])	[illegible]
Details	`{c5}` ([illegible])	[illegible]
Details	`{c6}` ([illegible])	[illegible]
Footer	`{c7}` ([illegible])	[illegible]

✔ [illegible] [illegible] [illegible] [illegible] [illegible], [illegible] [illegible] [illegible] [illegible] [illegible] [illegible]

✔ [illegible] [illegible] [illegible] [illegible] [illegible] [illegible]

Revision #6
Created 14 February 2025 02:12:11 by khn001029
Updated 17 February 2025 04:34:33 by khn001029